

Paper weight-110# (minimum)

Black nonfading ink required

# U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:  
T. 4 N. R. 10 E. 4th P.M.  
CORNER CODE INDEX

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT  
REV 10/23/2004 USMONREC.DWG

UNION TWP  
ROCK COUNTY WI

IF AVAILABLE  
ROCK COUNTY COORDINATES PREFERRED

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	A
B		6				5				4				3				2				1				B
C																										C
D																										D
E																										E
F																										F
G																										G
H																										H
J																										J
K																										K
L																										L
M																										M
N																										N
O																										O
P																										P
Q																										Q
R																										R
S																										S
T																										T
U																										U
V																										V
W																										W
X																										X
Y																										Y
Z																										Z

North \_\_\_\_\_ Elev. \_\_\_\_\_

East \_\_\_\_\_

Hor. Datum \_\_\_\_\_ Vert. Datum \_\_\_\_\_

LATITUDE \_\_\_\_\_ ELLIPS. HT. \_\_\_\_\_

LONGITUDE \_\_\_\_\_

NAD83(91) \_\_\_\_\_ NETWORK ADJ. YR 2010

GPS (X) \_\_\_\_\_ TRAVERSE (X) X

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL  AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT       WITNESS MONUMENT

BEARINGS ARE BASED ON: ROCK COUNTY PROJECTION

NE COR SEC 24  
T4N R9E  
GREEN COUNTY

FIELD BOOK \_\_\_\_\_ PAGE # \_\_\_\_\_

OR OBSERVATION SHEET \_\_\_\_\_

SHEET 1 OF 2

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE J/K -1

UN 6573 NE COR SEC 24 T4N R9E GREEN COUNTY

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1833 MULLETT (SEP) NORTH ON EAST SIDE OF SEC 24  
2640 SET 1/4 SECTION POST MADE A MOUND  
5280 SET POST FOR CORNER TO SECTIONS 13 & 24  
AND MADE A MOUND.  
LAND @ C SAME  
NEEDLE ATTRACTED 75' WEST  
NORTH ON EAST SIDE SECTION 13  
2640 SET 1/4 SECTION POST MADE A MOUND  
2937 ROAD FROM MINERAL POINT TO KOSCONONG E &  
W  
4620 LEAVE PRAIRIE  
5280 SET POST FOR CORNER TO SECTIONS 12&13 BUR  
OAK 24 S17E 80.52' & BUR OAK 12 N43E 89.76'  
LAND ROLLING RICH DRY PRAIRIE NORTH OF  
PRAIRIE THINLY TIMBERED WITH BUR OAK  
NEEDLE ATTRACTED 100' WEST
- 1833 BRINK PG 44 EAST BOUNDARY T4N R9E NORTH ON EAST  
SIDE OF SECTION 13  
2640.00 SET 1/4 SECTION POST IN PRAIRIE MADE A  
MOUND  
2937.00 ROAD FROM MINERAL POINT TO KOSCONONG  
E&W  
4620.00 LEAVE PRAIRIE  
5280.00 SET POST FOR CORNER TO SECTIONS 12 & 13  
BUR OAK 24 S17E 80.52'; BUR OAK 12 N43E  
89.76' LAND ROLLING RICH DRY PRAIRIE.  
NORTH OF PRAIRIE THINLY TIMBERED WITH  
BURR OAK NEEDLE ATTRACTED 1-40 WEST
- 1833 HARRISON T4N T10E 4TH MER WEST BETWEEN SECS 7 &  
18  
1114.08 BURR O 12  
1980.0 LEAVE TIMBER & ENTER PRAIRIE  
2640.00 QUARTER SEC COR SET POST & RAISED MOUND  
5396.16 INT. WEST BDY SET COR TO SECS 7 & 18 SET  
POST & RAISED MOUND LAND 1ST 1980' LEVEL  
2ND RATE WITH BURR O TIMBER RUN LEVEL 1ST  
RATE PRAIRIE
- 1833 HARRISON T4N T10E 4TH MER WEST BETWEEN SECS 7 &  
18  
1114.08 BURR O 12  
1980.0 LEAVE TIMBER & ENTER PRAIRIE  
2640.00 QUARTER SEC COR SET POST & RAISED MOUND  
5396.16 INT. WEST BDY SET COR TO SECS 7 & 18 SET  
POST & RAISED MOUND LAND 1ST 1980' LEVEL  
2ND RATE WITH BURR O TIMBER RUN LEVEL 1ST  
RATE PRAIRIE
- 1870 RUGER AUG REMON-90 NORTH ON WEST LINE OF SW 1/4  
SEC 18 ON A VAR 5-45; AT  
2636.04 INTERSECTED QUARTER LINE AT QUARTER  
CORNER. FOUND LIME STONE AT CORNER SET BY  
SELF IN A PREVIOUS SURVEY.  
NORTH ON WEST LINE OF NW 1/4 SEC 18  
ON A VAR 5-30; AT  
2637.03 INTERSECTED NORTH BOUNDARY LINE AT  
CORNER.
- 1978 TALARCZYK #5145 ALUMINUM MON. CORNER SET BY  
PROPORTIONATE MEASUREMENT & EXISTING PHYSICAL  
EVIDENCE. REFERENCED SAME.
- 1977 BARNES FB#1 PG 28 & 29 FD ALUM. MON. 1763.47 TO  
CUT LS @ W 1/4 COR SEC 18 T4N R10E.

SEAL

SHEET 1 OF 2

Embloss  
Arnold  
Barnes

CORNER CODE J/K-1

Aug 17, 2011

UN 6573 NE COR SEC 24 T4N R9E GREEN COUNTY

1996 BOWEDEN GPS LAT 42-48-48.894285 LONG 89-22-  
09104720 [ REDUCED TO 316,896.95; 400,300.48] ELEV  
961.66

USED 1977 FIELD DATA TO COMPUTE COORDINATES.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

DID NOT ACCEPT NOR REJECT ALUM FOUND IN 1977.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

*Donald Barnes*

SEAL

SHEET 2 OF 2

Emboss

Aug 17 2011

CORNER CODE J/K-1

A.E. 7.08 REQUIREMENT