

Paper weight-110# (minimum)

Black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:
T. 4 N. R. 10 E. 4th P.M.
CORNER CODE INDEX

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT
REV 10/23/2004 USMONREC.DWG

UNION TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	A
B		6				5				4				3				2				1				B
C																										C
D																										D
E																										E
F																										F
G																										G
H																										H
J																										J
K																										K
L																										L
M																										M
N																										N
O																										O
P																										P
Q																										Q
R																										R
S																										S
T																										T
U																										U
V																										V
W																										W
X																										X
Y																										Y
Z																										Z

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

NAD83(91) _____ NETWORK ADJ. YR 2010

GPS (X) _____ TRAVERSE (X) X

BASED ON THE FOLLOWING CONTROL:

◆ CORNER MONUMENT

○ WITNESS MONUMENT

BEARINGS ARE BASED ON: --- ROCK COUNTY PROJECTION ---

FIELD BOOK _____ PAGE # _____
OR OBSERVATION SHEET _____

SHEET 1 OF 5

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE R-21

UN591 NECORSEC26

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1833 HARRISON T4N R10E 4TH MER. NORTH BETWEEN SECS 25 & 26

1650. LEFT PRAIRIE & ENTER TIMBER
2640.00 QUARTER SEC. COR. {BURR O 48 N89R 5.94'; BURR O 10 N70W 19.14'?? BURR O 18 & BURR O 10} MARKED
5280.00 SET COR TO SECS 23,24,25,26 {BURR O 18 S33W 20.46', BURR O 18 S22E 208.56'; BURR O 18 N30E 45.54'; BURR O 18 N W 19.14' LAND ROLLING 2ND RATE ??? BRO?? TIMBER RED BURR AND W.O. MOSTLY GRASS ?? & WEEDS

1833 HARRISON (NOV5) T4N R10E EAST ON RAND. BET SECS 24 & 25

2640.0 TEMPY 1/4 POST
5205.42 INT. EAST BDY 52.80' NORTH OF POST LAND ROLLING 2ND RATE TIMBER WHITE & BURR OAK INDY, ?? GRASS, & WEEDS
WEST COR WEST BE. 24 & 25
2602.71 QUARTER SEC. COR
BURR OAK 18 N67W 34.98'; WHITE OAK 24 N52E 49.5' {BURR OAK 18; WHITE OAK 24} MARKED
5205.42 SEC COR.

1833 HARRISON (NOV5) T4N R10E EAST ON RAND 23 & 26

2640.00 TEMPY 1/4 SEC COR.
5247.00 INT. E BDY 2.64' N OF P LAND ROLLING 2ND RATE TIMBER W. & BURR O. ??? GRASS & WEEDS

WEST COR WEST BET SEC 23 & 26

2623.50 QUARTER SEC COR. {BYRR I 18 S16E 26.4' BURR O 18 N83E 42.24' BURR O 18 & BURR O 18} MARKED
5247.00 SEC OR.

1833 HARRISON (NOV5) T4N R10E NORTH BET SECS 22 & 23

2640.00 QUARTER SEC COR. {BURR O 12 S60W 25.74'; BURR O. 18 N64W 64.68' BURR O 12 & BURR O 12} MARKED
4062.96 BURR O 18
5280 COR TO SECS 14,15,22,23

{BURR O 12 S23W 36.3', BURR O 10 N20E 24.42', BURR O 10 N50W 17.16'; BURR O 12 S65E 14.52' LAND ROLLING 2ND RATE TIMBER ALL BURR O. MOSTLY SCRUB GRASS & WEEDS

1865 LOCKE VOL 1 PG 232 & 5199 FD BTS & REMAINS OF OLD STAKE - SET STAKE 2641.85 TO FD STAKE @ N 1/4 COR SEC 26 & VAR 7-32 2662.97 TO SET STAKE OVER HH 13X9X7 1/2 @ E 1/4 COR SEC 26

1865 LOCKE VOL 1 PG 233 SEC SEC 26. 2662.44 TO W 1/4 COR SEC 25

1870 RUGER AUG 17 REMON-65 NORTH ON WEST LINE OF SW 1/4 SEC 25 ON A VAR 7-02 OFFSET WEST 18.48' AT

2654.36 INTERSECTED QUARTER LINE 28.38' WEST OF QUARTER CORNER FOUND STAKE WITH STONE ON TOP OF IT SET BY LOCKE AT CORNER. ALSO FOUND WEST BEARING TREE AND STUMP OF EAST BEARING TREE.

COR VAR 6-49 AUGUST 18, 1870 NORTH ON WEST LINE OF NW 1/4 SEC 25 ON A VAR 7-08 OFFSET WEST 11.88' OFFSET WEST 3.63' AT

Donald Bruce
SEAL
Emboss
May 27, 2011

SHEET 1 OF 5

CORNER CODE R-21

- 2663.76 INTERSECTED NORTH BOUNDARY LINE 1.65' EAST OF COR. FOUND OLD STAKE AT CORNER. TESTED IT AND FOUND IT CORRECT. COR VAR 7-25
- 1870 RUGER AUG18 REMON-66 EAST ON NORTH LINE OF NW 1/4 SEC 25 ON A VAR 6-50 OFFSET NORTH 17.82' AT
 - 2620.20 INTERSECTED QUARTER LINE 17.16' NORTH OF QUARTER CORNER FOUND OLD STAKE AT CORNER ALSO FOUND STUMPS OF EAST BEARING TREE AND REMAINS OF STUMP OF WEST BEARING TREE. COR VAR 5-51
 - EAST ON NORTH LINE OF NE 1/4 SEC 25 ON A VAR 6-50 OFFSET NORTH 17.16' OFFSET NORTH 9.9' AT
 - 2614.92 INTERSECTED EAST BOUNDARY LINE 38.94' NORTH OF CORNER FOUND STAKE AT CORNER. ALSO FOUND NORTH BEARING TREE AND STUMP OF SOUTH BEARING TREE. COR VAR 6-35
- 1870 RUGER AUG REMON-67 WEST ON NORTH LINE OF NE 1/4 SEC 26 ON A VAR 6-40 AT
 - 2647.26 INTERSECTED QUARTER LINE 22.44' NORTH OF QUARTER CORNER. FOUND STAKE AND STONE ON CORNER. ALSO FOUND STUMPS OF BOTH BEARING TREES. COR VAR 7-09
 - WEST ON NORTH LINE OF NW 1/4 SEC 26 ON A VAR 6-58 OFFSET NORTH 15.18' OFFSET SOUTH 33' AT
 - 2650.56 INTERSECTED WEST BOUNDARY LINE 11.22' SOUTH OF CORNER FOUND REMAINS OF OLD STAKE ALSO FOUND SOUTH BEARING TREE AND REMAINS OF STUMP OF NORTH BEARING TREE COR. VAR 7-07
- 1870 RUGER AUG REMON-74 SOUTH ON WEST LINE OF NW 1/4 SEC 24 ON A VAR 7-07 AT
 - 2661.78 INTERSECTED QUARTER LINE 4.62' EAST OF QUARTER CORNER FOUND OLD STAKE AT CORNER. ALSO FOUND STUMP OF EAST BEARING TREE. COR VAR 7-01'
 - SOUTH ON WEST LINE OF SW 1/4 SEC 24 ON A VAR 6-53 OFFSET EAST 11.55' AT
 - 2650.06 INTERSECTED SOUTH BOUNDARY LINE 3.3' EAST OF CORNER. COR VAR 7-04'
- 1875 RUGER VOL 2 PG 201 STONE MON
- 1940 SUNNY VOL 3 PG 463 FD STONE MON. 2656.2 TO FD REMAINS OF DECAYED STAKE BUT FD NO STONE @ E 1/4 SEC 23
- 1970 BATTERMAN VOL 4 PG 449 FD SQ LS @ FENCE COR. [EASTERLY] 1889.44 TO PIN IN CENTER OF TERRITORIAL RD, 2622.13 TO FD CUT STONE @ S 1/4 COR SEC 24, 2656.73 TO SET CI @ W 1/4 SEC 24. LS IS SOUTH OF CTH M.
- 1972 DOT CTH M #7430 PROJ E0624(16) SHEET 4.2 & 4.3 6" QUARRIED STONE
- 1975 COMBS GCM VOL 5 PG 2 FD STONE.
- 1981 COMBS GCM VOL 10 PG 477 FD STONE.
- 1982 COMBS GCM VOL 11 PG 86 FD STONE
- 1983 COMBS #5187 FD STONE MON S88-47-20W TO STONE @ S 1/4 COR SEC 23, N89-08-40E 831.70 TO SET PIPE (4.2' NORTH OF FENCE LINE) ON SEC LINE, & N1-17-55W ALONG SEC LINE

Emboss
Donald Barnes
 May 27, 2011

UN591 NECORSEC26

- 1985 BARNES VOL 6 PG 340 SHOWS RECORD DISTANCES
1985 COMBS #13214 FD STONE MON. SO-11-55E ALONG SEC LINE
1 178.30 TO SET PIN & WEST 1040.22 TO FD PIPE ON EAST
R/W LINE OF CTH M.
1991 COMBS CSM VOL 15 PG 253 FD STONE 2656.94 TO POLY
@ W 1/4 COR SEC 24
1991 COMBS CSM VOL 15 PG 325 FD STONE 2656.94 TO POLY
@ W 1/4 COR SEC 24
1992 COMBS CSM VOL 18 PG 94 FD CUT STONE 2656.94 TO
ALUM @ E 1/4 COR SEC 23
1993 COMBS P32 PG175 "MORNINGRIDGE ESTATES" FD STONE @
NW 25 & W 1/4 COR SEC 25. 2664.80 BETWEEN STONES.
1995 COMBS P-32 PG 252 "MORNINGRIDGE ESTATES FIRST
ADDISTION" FD STONE @ NW 25 & W 1/4 COR SEC 25.
2664.80 BETWEEN STONES
1995 COMBS P-32 PG 274 "MORNINGRIDGE ESTATES SECOND
ADDISTION" FD STONE @ NW 25 & W 1/4 COR SEC 25.
2664.80 BETWEEN STONES
1995 COMBS CSM VOL 18 PG 252 FD CUT STONE 2656.94 TO
ALUM @ E 1/4 COR SEC 23
1995 COMBS CSM VOL 18 PG 468 FD CUT STONE 2656.94 TO
ALUM @ E 1/4 COR SEC 23
1996 COMBS CSM VOL 19 PG 200 FD STONES @ NE COR SEC 26
& E 1/4 COR SEC 26. 2664.8X BETWEEN STONES. WEST
1040.22 TO PIN ON EAST R/W LINE OF CTH M & SO-11-55E
TO E 1/4 COR SEC 26
1996 COMBS P-32 PG 315 "MORNINGRIDGE ESTATES THIRD
ADDITION" FD STONE @ NW 25 & W 1/4 COR SEC 25.
2664.80 BETWEEN STONES.
1996 COMBS P-32 PG 317 "MORNINGRIDGE ESTATES FOURTH
ADDISTION" FD STONE @ NW 25 & W 1/4 COR SEC 25.
2664.80 BETWEEN STONES
1998 WALKER #8250 FD STONE. MON. N1-46-00E 2656.96 TO
ALUM MON @ W 1/4 COR SEC 24
1999 COMBS CSM VOL 23 PG 107 FD STONES @ NW & N 1/4 COR
SEC 25 2622.13 BETWEEN STONES.
2000 COMBS CSM VOL 23 PG 111 FD STONES @ NW & N 1/4 COR
SEC 25 2622.13 BETWEEN STONES. 732.39 TO REROD @
CENTER OF TERRITORIAL RD.
2001 COMBS CSM VOL 25 PG 183 #14297 FD STONE MON. WEST
1040.22 TO FD PIN ON EAST R/W LINE OF CTH M. FROM NE
COR SEC 26 SO-11-55E TO FD STONE MON @ E 1/4 COR
SEC 26. FROM NE COR SEC 26 SO-11-55E 230.00 TO SET
PIN & WEST 240.22 TO SET PINE
2003 COMBS P-32 PG 596 "CONIFER HILLS" FD STONES @ NW
COR SEC 25 & N 1/4 COR SEC 25. 2622.13 BETWEEN
STONES.
2003 COMBS P-32 PG 620 "CONIFER HILLS FIRST ADDITION" FD
STONES @ NW COR SEC 25 & N 1/4 COR SEC 25. 2622.13
BETWEEN STONES.
2004 COMBS CSM VOL 27 PG 270 FD STONES @ NW COR SEC 25 &
N 1/4 COR SEC 25. 2622.13 BETWEEN STONES.
2007 COMBS P-32 PG "CONIFER HILLS SECOND ADDITION" FD
STONES @ NW COR SEC 25 & N 1/4 COR SEC 25. 2622.13
BETWEEN STONES.

Donald
SEAL
E. LOSS
Carver
May 27, 2011

SHEET 3 OF 5

CORNER CODE **R-21**

UN591 NECORSEC26

2007 COMBS CSM VOL 31 PG 223 FD STONE @ NE COR SEC 26
& E 1/4 COR SEC 26. 2664.94 BETWEEN STONES.

2008 COMBS P-32 PG 848 "CONIFER HILLS THIRD ADDITION" FD
STONES @ NW COR SEC 25 & N 1/4 COR SEC 25. 2622.13
BETWEEN STONES. NW COR TO N 1/4 COR SEC 25 N89-24-
04E & NW COR SEC 25 S1-09-34E 1052.93 TO FD PIN

FD CUT SPLIT LENGTHWISE LIMESTONE 0.3' ABOVE GRADE
/CARSONITE POST ON WEST SIDE

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD L.S.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

NO

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.


SEAL
Embloss

SHEET 4 OF 5

May 27, 2011

CORNER CODE **R-21**

A.E. 7.08 REQUIREMENT

