

Paper weight-110# (minimum)

Black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 4 N. R. 10 E. 4th P.M.

REV 10/23/2004

USMONREC.DWG

CORNER CODE INDEX

UNION TWP

ROCK COUNTY WI

IF AVAILABLE

ROCK COUNTY COORDINATES PREFERRED

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	A
B		6				5					4				3					2					1	B
C																										C
D																										D
E																										E
F																										F
G																										G
H																										H
J																										J
K																										K
L																										L
M																										M
N																										N
O																										O
P																										P
Q																										Q
R																										R
S																										S
T																										T
U																										U
V																										V
W																										W
X																										X
Y																										Y
Z																										Z

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

NAD83(91) _____ NETWORK ADJ. YR 2010

GPS (X) _____ TRAVERSE (X) X

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

ROCK COUNTY PROJECTION
BEARINGS ARE BASED ON:

FIELD BOOK _____ PAGE # _____
OR OBSERVATION SHEET _____

SHEET 1 OF 1

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE 519(1)

UN550 N1/4CORSEC14

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1833 HARRISON EAST ON RAND. BET SECS 11 & 14
 - 825.0 LEAVE PRAIRIE BEARING N.E.
 - 2640.00 TEMPY 1/4 SEC COR
 - 4092.0 ENTER PRAIRIE
 - 5215.98 INT E BDY 9.24' N OF P LAND ROLLING 2ND RATE & ? PRAIRIE-WHICH IS 1ST RATE TIMBER OF WOODLAND ALL BUR O.
 - WEST COR WEST BET SECS 11 & 14
 - 2607.99 QUARTER SEC COR. {BURR O 8 NBE 47.52'; BURR O 8 NSOW 51.47' BURR O 8 & BURR O 8} MARKED
 - 5215.98 SEC COR
- 1870 RUGER AUG REMON-101 EAST ON NORTH LINE OF NW 1/4 SEC 14 ON A VAZR 7-20; OFFSET SOUTH 17.82' AT
 - 2630.10 INTERSECTED QUARTER LINE 16.5' SOUTH OF QUARTER CORNER. FOUND OLD STAKE AT CORNER. ALSO FOUND BOTH BEARING TREES. STAKE CORRECT. COR VAR 7-18' AUGUST 31, 1870
 - EAST ON NORTH LINE OF NE 1/4 SEC 14 ON A VAR 7-16'; OFFSET NORTH 23.1' AT
 - 2623.50 INTERSECTED EAST BOUNDARY LINE 22.44' NORTH OF CORNER. FOUND REMAINS OF OLD STAKE AT CORNER. COR VAR 7-17
- 1984 BARNES J-19 FD CUT LIMESTONE. SET CAST IRON ON EAST SIDE & CARSONITE POST. REFERENCED SAME
- 1995 COMBS CSM VOL 18 PG 240 FD CUT L.S. S89-55-30E 2631.27 TO CUT LS @ SE COR SEC 11 & NO-04-35W 1339.10 ALONG N/S 1/4 LINE.
- 1995 COMBS CSM VOL 18 PG 242 FD CUT L.S. S89-55-30E 2631.27 TO CUT LS @ SE COR SEC 11 & NO-04-35W 1339.10 ALONG N/S 1/4 LINE.
- 2008 LATHROP CSM VOL 32 PG 237 CUT STONE NO-03-43W 5355.05 TO FD PK @ N 1/4 COR SEC 11
- 2008 LATHROP #16081 CUT LS NO-03-43W 5355.05 TO FD PK @ N 1/4 COR SEC 11

FD CUT LIMESTONE & REFERENCE TIES WITH CARSONITE @ SE COR OF LIMESTONE.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD STONE.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

NONE

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location. NO

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

SHEET 1 OF 1

SEAL
Enlcep
Donald Barnes

CORNER CODE J-19(1)

Barnes

A.E. 7.08 REQUIREMENT

OCT 29 2011