

Paper weight-110# (minimum)

Black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:
T. 4 N. R. 10 E. 4th P.M.
CORNER CODE INDEX

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT
REV 10/23/2004 USMONREC.DWG

UNION TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	A
B		6				5				4				3			2				1					B
C																										C
D																										D
E																										E
F																										F
G																										G
H																										H
J																										J
K																										K
L																										L
M																										M
N																										N
O																										O
P																										P
Q																										Q
R																										R
S																										S
T																										T
U																										U
V																										V
W																										W
X																										X
Y																										Y
Z																										Z

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

NAD83(91) _____ NETWORK ADJ. YR 2010

GPS (X) _____ TRAVERSE (X) X

BASED ON THE FOLLOWING CONTROL:

◆ CORNER MONUMENT

○ WITNESS MONUMENT

BEARINGS ARE BASED ON: --- ROCK COUNTY PROJECTION ---

FIELD BOOK _____ PAGE # _____
OR OBSERVATION SHEET _____

SHEET 1 OF 3

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE E-7(1)

UN524 S1/4CORSEC5

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1833 (NOV) HARRISON (NOV 9) T4N R10E 4TH MER. EAST ON
RAND. BET. 5 & 8
2640.00 TEMPY 1/4 SEC COR
5365.14 INT E BDY 66.00' N OF P LAND ROLLING 2ND
RATE TIMBER BURR & W.O. GROWTH GRASS &
WEEDS
WEST COR WEST BET 5 & 8
2682.57 QUARTER SEC COR. {BURR O 12 N34E 66.00";
BURR O 11 S45W 133.98' BURR O 12 & BURR O
11} MARKED
5365.14 INT. SEC COR
- 1856 CHURCH VOL 1 PG 58 STATES NOTHING ABOUT MON.
2642.64 TO CENTER OF SEC 8 & 5285.28 TO S 1/4 COR
SEC 8
- 1856 CHURCH VOL 1 PG 61 STATES NOTHING ABOUT MON.
2768.70 TO SE COR SEC 5, 2617.56 TO SW COR SEC 5,
VAR 8 2640.00 TO CENTER OF SEC 5, & VAR 8 5214.0 TO N
1/4 COR SEC 5.
- 1870 RUGER AUG REMON-120 SEPTEMBER 8, 1870
WEST ON NORTH LINE OF NE 1/4 SEC 8 ON A
VAR 7-15; OFFSET SOUTH 16.50' AT
2808.30 INTERSECTED QUARTER LINE 11.88' SOUTH OF
QUARTER CORNER. FD OLD STAKE AT CORNER.
ALSO FD STUMP OF NORTH BEARING TREE AND
REMAINS OF STUMP OF SOUTH BEARING TREE.
COR. VAR 7-21
WEST ON NORTH LINE OF NW 1/4 SEC 8 ON A
VAR 8-30; OFFSET SOUTH 12.54' OFFSET NORTH
50.16' AT
2603.04 INTERSECTED WEST BOUNDARY LINE 27.06'
SOUTH OF COR. COR VAR 7-06
- 1892 BLEEDORN VOL 2 PG 429 & #5101 MON. 2808.96 TO MON @
NE COR SEC 8.
- 1976 BARNES VOL 5 PG 135 FD CUT STONE MARKED S 1/4.
CONCRETE FOR FENCE POST PAVED AROUND SOUTHERN
HALF OF MONUMENT. MONUMENT IS 1' DEEP, N SIDE OF
MONUMENT MEASURED 6". REF SAME. ON N/S FENCE LINE
TO THE SOUTH & ON NORTH SIDE OF FENCE INT.
- 1988 BARNES E-7 FD CUT LIMESTONE 1' DEEP. REFERENCED
SAME. ON LINE WITH N/S FENCE TO THE SOUTH
- 1988 BARNES #12708 FD LIMESTONE S1-17-02W 2668.78 INT 1/4
LINE & S1-17-02W 5320.50 TO LS @ S 1/4 COR SEC 8
- 1989 MILLER #12209 STATES NOTHING ABOUT MONUMENT BUT
SHOWS IT AS A SQUARE.
- 1998 BARNES E-7 FD CUT LIMESTONE 1.0 DEEP ON NORTH SIDE
OF E/W FENCE & ON LINE WITH N/S FENCE LINE TO THE
SOUTH. REFERENCED SAME.
- 2000 KARNS CSM VOL 23 PG 67 ROCK COUNTY SEC. COR. STATED
NOTHING ABOUT MON. 5321.44 TO ROCK COUNTY SEC. COR
@ S 1/4 COR SEC 8.
- 2011 DALSING CSM PRELIM FD CUT STONE. NO-07-55W 2654.66
TO CENTER OF SEC 5; NO0-07-55W 5229.28 TO FD CUT
STONE @ N 1/4 COR SEC 5.

FD CUT LIMESTONE 2' DEEP. 2" STEEL FENCE POST IS BROKE OFF.
BOTTOM IS ON THE SOUTH SIDE OF THE CUT L.S. PLACED 2
MAGNETS ON THE NORTH SIDE OF THE L.S. L.S. IS ON THE NORTH

SEAL

Emboss
Donald Beunes

May 27, 2011

SHEET 2 OF 3

CORNER CODE E-7(1)

UN524 S1/4CORSEC5

SIDE OF THE T-FENCE INT. SET CARSONITE POST ON NW SIDE OF STONE.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD CUT LIME STONE.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

NONE

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

NO

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

SEAL
Donald Barnes
EMLOS3

SHEET 2 OF 3

May 27, 2011

CORNER CODE E-7(1)

A.E. 7.08 REQUIREMENT

Paul Barnes
 EMBOSSED SEAL
 May 27 2011

FARM FIELD

325 +/-

120' +/-

4.6'
 SHEET 3 OF 3

E-7(1)

- 1/2X24 REROD
- FD 1 1/2 PIPE
- FD CUT L.S.
 2' DEEP WITH
 2" PIPE FENCE POST
 ON SOUTH SIDE,
 SET CARSONITE POST
 ON NW SIDE &
 2 MAGNETS ON
 NORTH SIDE OF
 FENCE INT.
 46" OAK
-

FENCE LINE IS GONE

1976 FB #1 PG 10
 1988 FB #2 PG 18
 OBSERVATION SHEET #34

S 1/4 COR
 SEC 5
 UNION TWP
 T4N R10E

