

Paper weight-110# (minimum)

Black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 4 N. R. 10 E. 4th P.M.

REV 10/23/2004

USMONREC.DWG

CORNER CODE INDEX

UNION TWP

ROCK COUNTY WI

IF AVAILABLE

ROCK COUNTY COORDINATES PREFERRED

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	A
B			6				5					4				3			2				1			B
C																										C
D																										D
E																										E
F																										F
G																										G
H																										H
J																										J
K																										K
L																										L
M																										M
N																										N
O																										O
P																										P
Q																										Q
R																										R
S																										S
T																										T
U																										U
V																										V
W																										W
X																										X
Y																										Y
Z																										Z

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

NAD83(91) _____ NETWORK ADJ. YR 2010 _____

GPS (X) _____ TRAVERSE (X) X

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT WITNESS MONUMENT

(a)

ROCK COUNTY PROJECTION
BEARINGS ARE BASED ON: -----

FIELD BOOK _____ PAGE # _____
OR OBSERVATION SHEET _____

SHEET 1 OF 3

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE v 9(1)

UN605 NECORSEC32

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1833 HARRISON T4N R10E 4TH MER EAST BET. SECS 28 & 33
 - 2640.00 TEMPY 1/4 SEC COR
 - 5256.24 INT E BDY 11.22 N OF P
 - LAND ROLLING 2ND RATE TIMBER ALL BURR O
 - WEST COR WEST BET SECS 28 & 33
 - 2614.92 QUARTER SEC COR {BURR O 12 S63W 40.92'; BURR O 18 N61E 33.66' BURR O 12 & BURR O 18} MARKED
 - 5256.24 SEC COR
- 1833 HARRISON T4N R10E 4TH MER EAST BET. SECS 29 & 32
 - 1980.0 LEAVE PRAIRIE & ENTER TIMBER
 - 2640.00 TEMPY 1/4 SEC COR
 - 5243.70 INT. E BDY 9.9' S OF P LAND 1ST 1/2 MILE ROLLING 1ST RATE PRAIRIE 2ND 1/4 LEVEL 2ND RATE WITH TIMBER OF BURR O. & UNDERGROWTH OF SCRUBS GRASS & WEEDS
 - WEST COR WEST BET SECS 29 & 32
 - 2621.85 QUARTER SEC COR {WO 12 N23E 50.82'; BURR O 14 N64W 122.76' WO 12 & BURR} MARKED
 - 5243.70 INT SEC COR.
- 1833 HARRISON T4N R10E NORTH BET SECS 32 & 33
 - 528.0 ENTER TIMBER
 - 2640.00 QUARTER SEC COR. {W.O. 14 N80E 68.64'; W.O. 24 S70W 91.08' WO 14 & WO 24} MARKED
 - 3300 ENTER MARSH CRS E & W
 - 5280.00 LEAVE IT AND SET COR TO SECS 28, 29, 22, & 33 {BURR O 14 N18E 48.84'; BURR O 12 N54W 51.48'; BURR O 12 S80W 66.00'; BURR O 12 S20E 13.86' LAND 1ST 1/2 MILE ROLLING 2ND RATE WITH BURR & W.O. TIMBER UNDERGROWTH SCRUBS GRASS & WEEDS.
- 1833 HARRISON T4N R10E 4TH MER NORTH BET. SECS 28 & 29
 - 1555.62 WO 18
 - 2640.00 QUARTER SEC COR. {WO 12 S79E 24.42'; WO 18 W 12.54' WO 12 & WO 18} MARKED
 - 5280.00 COR TO SECS 20, 21, 28, 29 {BURR O 10 S64E 273.24'; BURR O 12 S60W 234.96' LAND LEVEL 2ND RATE TIMBER BURR RED & W.O. UNDERGROWTH SCRUBS, GRASS, & WEEDS.
- 1870 RUGER AUG REMON-77 EAST ON SOUTH LINE OF SW 1/4 SEC 28 ON A VAR 6-50 OFFSET NORTH 12.54' AT
 - 2623.67 INTERSECTED QUARTER LINE 15.18' NORTH OF QUARTER CORNER. FD OLD STAKE IN CORNER. ALSO FD STUMP OF EAST BEARING TREE. COR VAR 6-46
 - EAST ON SOUTH LINE OF SE 1/4 SEC 28 ON A VAR 7-40 OFFSET NORTH 7.26'; OFFSET SOUTH 36.08' OFFSET NORTH 27.88' AT
 - 2666.40 INTERSECTED EAST BOUNDARY LINE 24.42' NORTH OF CORNER. COR VAR 7-10
- 1870 RUGER AUG REMON-81 NORTH ON WEST LINE OF SW 1/4 SEC 33 ON A VAR 6-45 OFFSET WEST 12.21' AT
 - 2655.18 INTERSECTED QUARTER LINE 11.22' WEST OF QUARTER CORNER. FOUND OLD STAKE SURROUNDED BY HAR HEAD STONES AT CORNER. ALSO FOUND STUMP OF WEST BEARING TREE AND WHERE STUMP OF EAST BEARING TREE HAD BEEN DUG UP. COR VAR 6-46

Ronald Barnes
 SEAL
 OCT 20, 2011

UN605 NECORSEC32

- NORTH ON WEST LINE OF NW 1/4 SEC 33
ON A VAR 7-07 OFFSET WEST 16.5' WEST
4.62' OFFSET WEST 38.61' AT
- 2658.48 INTERSECTED NORTH BOUNDARY LINE 44.88'
WEST OF CORNER. COR VAR 7-27'
- 1870 RUGER AUG REMON-77 EAST ON SOUTH LINE OF SW 1/4
SEC 28 ON A VAR 6-50 OFFSET NORTH 12.54'
AT
- 2623.67 INTERSECTED QUARTER LINE 15.18' NORTH OF
QUARTER CORNER. FD OLD STAKE IN CORNER.
ALSO FD STUMP OF EAST BEARING TREE. COR
VAR 6-46
EAST ON SOUTH LINE OF SE 1/4 SEC 28 ON A
VAR 7-40 OFFSET NORTH 7.26'; OFFSET SOUTH
36.08' OFFSET NORTH 27.88' AT
- 2666.40 INTERSECTED EAST BOUNDARY LINE 24.42'
NORTH OF CORNER. COR VAR 7-10
- 1870 RUGER AUG REMON-78 WEST ON NORTH LINE OF NE 1/4
SEC 32 ON A VAR 6-40' OFFSET NORTH 16.5' AT
- 2621.85 INTERSECTED QUARTER LINE 31.68' NORTH OF
QUARTER CORNER. FOUND REMAINS OF OLD
STAKE AT CORNER. ALSO FOUND REMAINS OF
BOTH STUMPS OF BEARING TREES. COR VAR 7-
00
WEST ON NORTH LINE OF NW 1/4 SEC 32
ON A VAR 7-05 OFFSET NORTH 8.74'
OFFSET SOUTH 37.95' AT
- 2625.15 INTERSECTED WEST BOUNDARY LINE 11.72'
NORTH OF CORNER. FOUND HARD HEAD STONE
AT CORNER SET BY SELF IN A PREVIOUS SURVEY.
COR VAR 7-58
- 1870 RUGER AUG REMON-77 SOUTH ON WEST LINE OF NW
1/4 SEC 28 ON A VAR 7-05 OFFSET EAST 1.98' AT
- 2665.41 INTERSECTED QUARTER LINE 5.94' EAST OF
QUARTER CORNER. FOUND OLD STAKE AND BOTH
STUMPS OF BEARING TREES. COR VAR 7-00'
SOUTH ON WEST LINE OF SW 1/4 SEC 28
ON A VAR 7-20 OFFSET EAST 11.22'
OFFSET WEST 19.14' OFFSET EAST 17.16'
AT
- 2661.28 INTERSECTED SOUTH BOUNDARY LINE 4.62' WEST
OF CORNER FOUND STUMPS OF BOTH BEARING
TREES. ESTABLISHED CORNER FROM STUMPS OF
BEARING TREES. COR VAR 7-38
- 1900 BROWN VOL 2-518 FD MONUMENT BUT STATES NOTHING
ABOUT IT. 2625.48 TO N 1/4 COR SEC 32.
- 1906 KERCH VOL 3 PG 36 FD MONUMENT. 2628.8 TO FD MON @
N 1/4 COR SEC 33
- 1938 SUNNY VOL 3 PG 373 FD STONE MONUMENT.
- 1994 BARNES V-9 FD CUT LIMESTONE. PLACED MAGNETS
ABOUT 15" DEEP NEXT TO LIMESTONE. REFERENCED SAME.
@ FENCE INT.
- 1997 COMBS CSM VOL 20 PG 152 CUT STONE. NO-06-35W
2662.66 TO CI @ E 1/4 COR SEC 29. SET 1/16TH COR MID
WAY IN RD.
- 1997 COMBS CSM VOL 20 PG 288 CUT STONE. NO-06-35W
2662.66 TO CI @ E 1/4 COR SEC 29.
- 2003 COMBS BK 32 PG 587 BERG WOODWORTH & PETERSON
SUB. LS 2628.83 TO ALUM @ S 1/4 COR SEC 28

Seal
Emboss
R. J. Frazer
OCT 20, 2011

SHEET 2 OF 3

CORNER CODE V-9(1)

UN605 NECORSEC32
2004 COMBS CSM VOL 27 PG 266 BERG WOODWORTH &
PETTERSON SUBDIVISION" LS S89-48-15E 2628.83 TO ALUM
@ S 1/4 COR SEC 28
2004 COMBS BK32 PG 666 BERG WOODWORTH & PETTERSON SUB.
FIRST ADD" LS S89-48-15E 2628.83 TO ALUM @ S 1/4 COR
SEC 28
2006 COMBS CSM VOL 30 PG 262 LS 2662.75 TO CI @ W 1/4 COR
SEC 28
2006 COMBS BK32 PG 778 WESTFIELD MEADOWS" LS 2628.83 TO
N 1/4 COR SEC 33

ACCEPTED MY 1994 FD CUT LIMESTONE AND REFERENCES. USED
MY OBSERVATIONS IN THE TOWNSHIP ADJUSTMENT.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

YES

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

NONE

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

NO

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.



SEAL
OCT 20, 2011
Emboss

SHEET 3 OF 3

CORNER CODE V-9(1)
A.E. 7.08 REQUIREMENT