

PLAT AND RECORD

COUNTY BUILDING
IN CITY OF BELOIT

Of a Survey on Section T R E. of the 4 P. M. in Township

Rock County, Wisconsin, made the 19

I hereby certify that the following is a correct record of said survey as made by me.

County Surveyor.

Bench	Back sight	Inst	Fore sight	Req	Inter sight	Heights	Remarks.
		19.628					
					16.030	3.598	S.W. Cor. of float Sec. of E. flume of Ford's Mill. Average 3.562 S line of float Sec.
					16.040	3.588	
					16.045	3.583	
					16.085	3.543	
					16.130	3.498	
					16.020	3.608	W. side, Middle line of float Sec. of E. flume Ford Mill. Average 3.621 Middle line of float Sec.
					16.030	3.598	
					15.965	3.663	
					16.000	3.628	
					16.020	3.608	
					16.040	3.588	N.W. Cor. of float Sec. E. flume of Ford's Mill. Average 3.541 N line of float Sec.
					16.080	3.548	
					16.075	3.553	
					16.080	3.548	
					16.160	3.468	
						3.575	Mean average of bottom of float Sec. of E. flume of Ford's Mill. There is a sill 4x4 inches at foot of E. side of flume to be taken from above.
16.217	4.334	20.551					Cut bench on upper surface of point of stone ice break E. side of chute.
			3.950	16.601			
	5.213	21.814					
15.034			6.780				Cut bench on upper surface of N. stone abutment to flume of Hodson's Mill.
	2.912	17.946					
6.982			10.964				
7.036			10.910				Bench on N. float Section of flume of Hodson's Mill.
15.034							Cut bench on upper surface of N. stone abutment to of Hodson's Mill.
	4.613	19.647					
7.995			11.652				
8.991			10.656				Bench on N. side of float Sec. of flume of Harvey's Mill.
15.034							Cut bench on upper surface of N. stone abutment to flume of Hodson's Mill.
	3.052	18.086					
			11.615	6.471			
	1.990	8.461					Bench on dump, S. of Bonner City Mills.
2.991			5.480				

Copied from P. 113 Vol. 2 Original County Surveyor's Record.